

MW4532C SERIES ~ Wire Wound Ferrite Chip Inductors




Wire Wound Chip Inductors Large Current

PART NUMBERING SYSTEM

MW	4 5 3 2 C	—	R 1 0 M	—	L F
TYPE	DIMENSIONS		INDUCTANCE		LEAD FREE

SHAPES AND DIMENSIONS

UNIT : mm



SPECIFICATION TABLE

PART NUMBER	INDUCTANCE (μ H)	Q. MIN.	TEST FREQ (MHz)	SRF (MHz) MIN.	DCR (Ω) (max)	IDC (mA) (max)
MW4532C-1R0K-LF	1.0±10%	10	7.96	200	0.11	1050
MW4532C-1R2K-LF	1.2±10%	10	7.96	160	0.12	1000
MW4532C-1R5K-LF	1.5±10%	10	7.96	130	0.15	950
MW4532C-1R8K-LF	1.8±10%	10	7.96	100	0.16	900
MW4532C-2R2K-LF	2.2±10%	10	7.96	80	0.18	850
MW4532C-2R7K-LF	2.7±10%	10	7.96	60	0.20	800
MW4532C-3R3K-LF	3.3±10%	10	7.96	45	0.22	750
MW4532C-3R9K-LF	3.9±10%	10	7.96	40	0.24	700
MW4532C-4R7K-LF	4.7±10%	10	7.96	35	0.27	650
MW4532C-5R6K-LF	5.6±10%	10	7.96	30	0.30	650
MW4532C-6R8K-LF	6.8±10%	10	7.96	28	0.35	600
MW4532C-8R2K-LF	8.2±10%	10	7.96	25	0.40	600



MW4532C SERIES ~ Wire Wound Ferrite Chip Inductors



Wire Wound Chip Inductors Large Current

SPECIFICATION TABLE

PART NUMBER	INDUCTANCE (μ H)	Q. MIN.	TEST FREQ (MHz)	SRF (MHz) MIN.	DCR (Ω) (max)	IDC(mA) (max)
MW4532C-100K-LF	10.0 \pm 10%	10	2.52	22	0.50	550
MW4532C-120K-LF	12.0 \pm 10%	10	2.52	21	0.60	500
MW4532C-150K-LF	15.0 \pm 10%	10	2.52	20	0.70	450
MW4532C-180K-LF	18.0 \pm 10%	10	2.52	19	0.80	400
MW4532C-220K-LF	22.0 \pm 10%	10	2.52	18	0.90	370
MW4532C-270K-LF	27.0 \pm 10%	10	2.52	16	1.2	330
MW4532C-330K-LF	33.0 \pm 10%	10	2.52	14	1.4	300
MW4532C-390K-LF	39.0 \pm 10%	10	2.52	12	1.6	280
MW4532C-470K-LF	47.0 \pm 10%	10	2.52	11.5	1.9	260
MW4532C-560K-LF	56.0 \pm 10%	10	2.52	11.0	2.2	240
MW4532C-680K-LF	68.0 \pm 10%	10	2.52	10.0	2.6	220
MW4532C-820K-LF	82.0 \pm 10%	10	2.52	9.0	3.5	200
MW4532C-101K-LF	100 \pm 10%	20	0.796	8.0	4.0	180
MW4532C-121K-LF	120 \pm 10%	20	0.796	7.5	4.5	160
MW4532C-151K-LF	150 \pm 10%	20	0.796	7.0	6.5	140
MW4532C-181K-LF	180 \pm 10%	20	0.796	6.5	7.5	120
MW4532C-221K-LF	220 \pm 10%	20	0.796	5.5	9	120
MW4532C-271K-LF	270 \pm 10%	20	0.796	5.0	11	100
MW4532C-331K-LF	330 \pm 10%	20	0.796	4.0	13	90
MW4532C-391K-LF	390 \pm 10%	20	0.796	3.8	23	80
MW4532C-471K-LF	470 \pm 10%	20	0.796	3.5	26	75
MW4532C-561K-LF	560 \pm 10%	20	0.796	2.8	30	70
MW4532C-681K-LF	680 \pm 10%	20	0.796	2.6	40	65
MW4532C-821K-LF	820 \pm 10%	20	0.796	2.5	45	60
MW4532C-102K-LF	1000 \pm 10%	20	0.796	2.3	50	55




MW4532C SERIES ~ Wire Wound Ferrite Chip Inductors




Wire Wound Chip Inductors Large Current

PACKAGING SPECIFICATION



	A	B	C	D	E	W8	W12	t	R
T($\psi 178\text{mm}$) Reel	$\psi 178 \pm 2$	$\psi 60 \pm 1$	$\psi 13 \pm 0.8$	$\psi 21 \pm 0.8$	2	10 ± 1.5	14.5 ± 1.5	1.27 ± 0.2	1



TYPE	A	B	T	t	T($\psi 178\text{mm}$)	T($\psi 330\text{mm}$)
MW4532C	3.60	4.90	2.05	0.3	500 pcs/reel	-